NOS-6369 – Test & Flush HPU

PLS Controlled

Specifiction



NOS Test & flushing HPU's are a range off HPU's built with two pumps. One for high pressure & one for high flow to do testing and flushing with one unit. The HPU's are fully automated and controlled by touch screen.

HPU in Frame		
Approvals	Norsok Z-015, DNV 2.7-1	
Area Classification	ATEX Sone 1, IIB T3	
Frame Size	1500x1500x2050mm (LxWxH)	
Weight	1 600kg	
Z-015 Type	U99	
Flow & pressure		
	LP	HP
Pump Type	MarshalSea XW1197-43	MarshalSea XW1196-50
Electric motor	5,5Kw	15Kw
Flow	0-1,9 lpm	0-16,5 lpm
MWP	690 bar	345 bar
Accumulator	25L	10L
Process data		
HMI	9" touch Screen	
Flow control	Frequency control	
PRV	Yes	
Tank	200L	
Filter LP	DHD110H03B	
Filter HP	DHD60H03B	
Filter Return	DHD660G03	
Pump Lubrication	Castrol Alfasyn HW150	
Supply connection		
Outlet HP	3/8" MP	
Outlet LP	½" Tube / fitting on request	
Return / Fill	1 " Tube / fitting on request	
Purge Air	1" Claw	
Power	400/440v,63A 50/60Hz	
Ambient Operating temperature	0 – 60 °C (below 0°C contact NOS)	

NOS Rental Forusbeen 226
4313 Sandnes
TLF: 51733000